

Cordless FlexShade®

Cordless, manual roller shade with decorative headrail

SUBMITTAL TECHNICAL INFO

Please check all appropriate selections and attach room schedule with verified dimensions.

CORDLESS FLEX

Fabric Series: _____

Color Name / Number: _____

Openness Factor: _____


Please see [Fabric Options](#) on the [Draper® website](#) for fabric colors and specifications.

Select Fabric Orientation


- Regular Roll (from back of roller) (standard)
- Reverse Roll (from front of roller)

Select Mounting Style

- Inside Mount
- Outside Mount



INSIDE MOUNT



OUTSIDE MOUNT

Select Hem Bar Style

- Closed Pocket - 1" (25mm) Elliptical Slat (standard)
- Open Pocket - 1" (25mm) Elliptical Slat
- Flat Rectangular Exposed Hem Bar
 - Small - 7/8" x 5/16" (22mm x 8mm)
 - Large - 1 1/2" x 5/16" (38mm x 8mm)
- Small Round Exposed Hem Bar - 3/4" (19mm) diameter

Available Sizes:

WIDTH:	2'	3'	4'	5'	6'	7'	8'
HEIGHT	2'						
3'							
4'							
5'							
6'							
7'							
8'							

Fabric weight and thickness will determine maximum shade size.

Specifications

MANUALLY-OPERATED WINDOW SHADES WITH INDEPENDENT CONTROL: ANSI/WCMA A100.1 compliant, manually-operated, vertical roll-up, fabric window shade with components necessary for complete installation; Cordless FlexShade® roller-operated shade as manufactured by Draper, Inc.

OPERATION: Spring roller operating mechanism with metal roller containing heavy-duty spring with positive locking mechanism permitting shade to be stopped at each half turn of roller. Spring sized by manufacturer to accommodate shade size.

MOUNTING BRACKETS: Metal. Provide size compatible with roller size. Mounted to [ceiling] [wall] [jamb].

ROLLER TUBE: Fabricated from extruded aluminum. Roller outer diameter 1.5 inches (38 mm).

FABRIC TO TUBE ATTACHMENT: Connected to the roller tube with LSE (low surface energy) double sided adhesive specifically developed to attach coated textiles to metal. Adhesive attachment to eliminate horizontal impressions in fabric.

ROLLER SPRING TENSION: To be adjustable from the roller brackets to ensure correct tension for proper retraction.

HEM BAR:

CLOSED POCKET ELLIPTICAL SLAT: 1" (25mm) aluminum elliptical slat inside of a 1 1/8" (41mm) pocket with heat sealed ends.

OPEN POCKET ELLIPTICAL SLAT: 1" (25mm) aluminum elliptical slat with plastic ends inside of a 1 1/8" (41mm) pocket.

FLAT EXPOSED HEM BAR: SMALL: 7/8" x 5/16" (22mm x 8mm) and **LARGE:** 1 1/2" x 5/16" (38mm x 8mm) aluminum rectangular hem bar with plastic endcaps. Powder coated in black, bronze, ivory, white, or clear anodized.

SMALL ROUND EXPOSED HEM BAR: 3/4" (19mm). Aluminum with plastic end caps.

DOWNLOADABLE 3-PART SPECIFICATIONS:

available at www.draperinc.com

Please note: Dimensions of rollers, operators, and hardware at manufacturer's discretion.



Draper, Inc. | 411 S. Pearl St. Spiceland, IN 47385
draperinc.com | 765.987.7999 | 800.238.7999

© 2021 All Rights Reserved | FORM: FlexShade_Cordless_Sub21

PROJECT: _____

ARCHITECT: _____

CONTRACTOR: _____

SUPPLIER: _____

DATE: _____ REVISED: _____

Components

